

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
14 December 2000 (14.12.2000)

PCT

(10) International Publication Number  
WO 00/74883 A1

- (51) International Patent Classification<sup>7</sup>: B23B 5/02, B60B 27/00
- (21) International Application Number: PCT/US00/14187
- (22) International Filing Date: 23 May 2000 (23.05.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
09/329,003 9 June 1999 (09.06.1999) US
- (71) Applicant: THE TIMKEN COMPANY [US/US]; 1835 Dueber Avenue, S.W., Canton, OH 44706-0930 (US).
- (72) Inventor: LAPS, Larry, D.; 134 Shoreline Drive, Canton, OH 44708 (US).
- (74) Agent: BOESCHENSTEIN, Edward, A.; Polster, Lieder, Woodruff & Lucchesi, L.C., 763 South New Ballas Road, St. Louis, MO 63141 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— With international search report.  
— Before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: HUB ASSEMBLY HAVING MINIMUM RUNOUT AND PROCESS FOR PRODUCING THE SAME



(57) Abstract: An automotive hub assembly (A), which carries a brake disk (B), has a hub (2) provided with a spindle (12) which rotates in a housing (4) on a double row antifriction bearing (6) having its raceways (28, 44) oriented obliquely to the axis (X) of rotation so that the bearing (6) accommodates both radial and axial loads. The bearing is set to a condition of preload so no free motion exists in it. The hub also has a flange (10) at one end of its spindle, and the flange is machined on its face that is presented away from the housing to provide a machined mounting surface (22) against which the brake disk is installed. The machining occurs after the hub assembly is assembled. To this end, the housing of the hub assembly is held fast while the hub is rotated on the bearing. With the hub rotating, a cutting tool (70) is moved across the face of the flange, and it produces the machined mounting surface which is perpendicular to the axis of the bearing. The machined mounting surface has essentially no runout, so that the brake disk acquires no runout from the hub assembly.

## HUB ASSEMBLY HAVING MINIMUM RUNOUT AND PROCESS FOR PRODUCING THE SAME

### Technical Field

5           This invention relates in general to hub assemblies, and more particularly to a hub assemblies with surfaces that rotate with essentially no runout and a process for producing the same.

          Most passenger automobiles and light trucks of current manufacture come equipped with disk brakes, at least at the front wheels of such vehicles.  
10   Disk brakes weigh less than drum brakes, which they have to a large measure replaced, are less expensive to manufacture, are easier to service, and provide more effective braking. But disk brakes will produce annoying pulsations, known as "brake judder" if improperly manufactured or maintained.

### Background Art

15           The typical disk brake for a vehicle has a disk which rotates with a road wheel of the vehicle and a caliper which clamps down on the disk when the brakes of the vehicle are applied. Indeed, the caliper has pads which bear against machined surfaces on two sides of the disk, with the friction between the pads and the machined surfaces providing the braking. The machined surfaces  
20   must be perfectly flat, and must rotate without runout (wobble), lest brake judder will develop when the brakes are applied.

          Various arrangements exist for mounting the road wheels – and the brake disks as well – on the suspension systems of the vehicles. In one the road wheel and brake disk for that wheel are bolted to a hub having a spindle which  
25   rotates in an antifriction bearing which in turn is fitted to a housing. The housing is attached to a steering knuckle or other component of the vehicle's suspension system. The disk, being a separate and relatively simple component is easily machined to close tolerances along its critical surfaces. But that surface of the hub against which the brake disk is installed does not lend itself  
30   to the same precision. To be sure, it is machined, but the machining occurs before assembly, so the bearing on which the hub rotates and the surface on

which it is mounted can all contribute to runout in the surface against which the brake disk is installed. This runout transfers to the brake disk itself.

#### Summary of the Invention

5 The present invention resides in a process for providing the rotating hub of a hub assembly with a mounting surface that is essentially free of runout, so that a brake disk installed against that surface will not acquire runout from the hub assembly. The hub has a spindle which rotates on a bearing in a housing, both of which also form part of the hub assembly. At one end of the spindle the hub has a flange provided with a face which is presented away from the  
10 housing. That face is machined while the housing is held fast and the hub is rotated on the bearing, and as a consequence the face, which is the mounting surface, rotates with essentially no runout. The invention also resides in a process for assembling a hub assembly and also in the hub assembly itself.

#### Brief Description of Drawings

15 In the accompanying drawings which form part of the specification and wherein like numerals and letters refer to like parts wherever they occur:

Fig. 1 is a sectional view of a hub assembly constructed in accordance with and embodying the present invention, with the hub assembly being fitted to a steering knuckle and having a brake disk and road wheel mounted on it;

20 Fig. 2 is a sectional view of the hub assembly showing the mounting surface of the flange on its hub being machined before threaded studs are fitted to the flange;

Fig. 3 is a partial end view of the mounting surface on the flange of the hub; and;

25 Fig. 4 is a sectional view of the hub assembly showing the mounting surface on the flange of its hub being machined while the studs are in the flange.

#### Best Mode for Carrying Out the Invention

Referring now to the drawings (Fig. 1), a hub assembly A is mounted on a component C of the suspension system for an automotive vehicle and enables  
30 a road wheel W to rotate relative to the component C about an axis X of rotation. Not only does the hub assembly A have the road wheel W attached to

it, it also carries a brake disk B which likewise revolves about the axis X. Indeed, the disk B rotates with essentially no runout at its critical friction surfaces, to a large measure this being a consequence of a machining procedure used during the manufacture of the hub assembly A.

5        Considering the hub assembly A first, it includes (Fig. 1) a hub 2, a housing 4, and a bearing 6 which enables the hub 2 to rotate relative to the housing 4 about the axis X with relatively little friction. The road wheel W and brake disk B are attached to the hub 2, while the housing 4 is secured firmly against the component C of the vehicle suspension system. The component C  
10       may be a steering knuckle.

      The hub 2 has (Fig. 1) a flange 10 and a spindle 12 which projects from one face of the flange 10. Actually spindle 12, which contains a through bore 14, emerges from a shoulder 16 located along the inside face of the flange 10 and terminates at an outwardly directed formed end 18 located at its opposite  
15       end. Radially beyond the spindle 12 the flange 10 contains threaded studs 20 which project axially from its other face. That face is machined to provide a mounting surface 22 against which the brake disk B fits, and indeed the disk B takes its orientation from the surface 22. The disk B fits over the studs 20 as does the road wheel W, and lug nuts 24 thread over the studs 20 to secure the  
20       brake disk B and road wheel W firmly to the hub 2.

      The bearing 6 includes (Fig. 1) an inner race in the form of two cones 26 which fit around the spindle 12 where they are captured between the shoulder 16 and the formed end 18, there being an interference fit between each cone 26 and the spindle 12. Each cone 26 has a tapered raceway 28 that is presented  
25       outwardly away from the axis X, a thrust rib 30 at the large end of its raceway 28, and a back face 32, which is squared off with respect to the axis X, on the end of the thrust rib 30. The inboard cone 26 is somewhat longer than the outboard cone 26 by reason of having a cylindrical cone extension 34 which projects beyond the small end of its raceway 28. The inboard cone 26 at its  
30       cone extension 34 abuts the small end of the outboard cone 26 along the spindle 12, that is to say, the two cones 26 abut at their front faces. The back face 32 of

the outboard cone 26 abuts the shoulder 16 that lies along the flange 10. The formed end 18 turns outwardly over and against the back face 32 of the inboard cone 26 and serves to capture the two cones 26 on the spindle 12.

In addition to the cones 26, the bearing 6 includes (Fig.1) tapered rollers 40, arranged in two rows, there being a separate row around each cone 26. Actually, the rollers 40 extend around the raceways 28 for the cones 26, there being essentially line contact between the tapered side faces of the rollers 40 and the raceways 28. The large end faces of the rollers 40 bear against the thrust ribs 30. The rollers 40 of each row are essentially on apex, which means that the envelopes in which their tapered side faces lie have their apices located at a common point along the axis X. Each row of rollers 40 has a cage 42 to maintain the proper spacing between the rollers 40 in that row.

The ring-like housing 4 surrounds the spindle 12 as well as the two cones 26 and the two rows of rollers 40 (Fig. 1). It forms part of the bearing 6 in that it has tapered raceways 44 which are presented inwardly toward the axis X. Indeed, the housing 4 constitutes the outer race of the bearing 6. The raceways 44 on the housing 4 taper downwardly toward an intervening surface which separates them. The rollers 40 likewise lie along the raceways 44 of the housing 4, there being essentially line contact between the raceways 44 and the tapered side faces of the rollers 40. At their large ends, the raceways 44 open into short end bores 46 in which the thrust ribs 30 of the two cones 26 are located.

Generally midway between its ends, the housing 4 has a triangular or rectangular flange 50 which fits against the component C of the suspension system for the vehicle. Here the housing 4 is secured firmly to the suspension system component C with bolts 48 that engage threaded holes 52 located in the lobes of the flange 50.

The end bores 46 in the housing 4 contain closures 54 which fit around the thrust ribs 30 on the cones 26 to establish fluid barriers at the ends of the housing 4.

These barriers isolate the rollers 40 and the raceways 28 and 44 from road contaminants, such as water, ice-melting salts and dirt. U.S. Patents 5,022,659 and 5,816,711 disclose suitable closures.

The formed end 18 unitizes the hub assembly A. But the hub 2 does not  
5 always have the formed end 18. Initially, the spindle 12 of the hub 2 extends from the shoulder 16 all the way to its end as a cylindrical surface. The two cones 26 with their complement of rollers 40 and the housing 4 captured between the rollers 40 of the two rows are installed over the cylindrical surface of the spindle 12 and advanced until the back face 32 of the outboard cone 26  
10 comes against the shoulder 16 at the other end of the spindle 12. A portion of the spindle 12 projects beyond the back face 32 of the inboard cone 26. This portion is deformed into the formed end 18. PCT application GB 98/01823 (International Publication No. WO98/58762), discloses a rotary forming process for upsetting the initially extended end of the spindle 12 and converting that end  
15 into the formed end 18 which captures the cones 26 on the spindle 12 and in effect unitizes the entire hub assembly A.

Other means may secure the two cones 26 on the spindle 12 as well. For example, the end of the spindle 12 may have threads and a nut engaged with those threads and turned down against the back face 32 of the inboard cone 26.  
20 Also, the end of the spindle 12 may have a groove and a snap ring fitted to the groove.

When the hub assembly A is so unitized, its bearing 6 exists in a condition of slight preload. Actually the spacing between the inner raceways 34 on the cones 26 determines the setting of the bearing 6, and that spacing  
25 depends on the length of the cone extension 34 for the inboard cone 26, inasmuch as the rotary forming procedure which produces the formed end 18 drives the inboard cone 26 toward the outboard cone 26 with enough force to cause the cone extension 34 on the former to abut the small end of the latter. Since the bearing 6 is set to a condition of preload and interference fits exist  
30 between its cones 26 and the spindle 12, the hub A rotates within the housing 4

without any radial or axial free motion. As a consequence, the axis X remains stable.

Only after the hub assembly A is unitized with its bearing 6 set in preload, is the outboard face of the flange 10 for the hub 2 machined to provide the mounting surface 22. But the machining occurs before the threaded studs 20 are installed in the flange 10. Indeed, before the machining and likewise before the installation of the bearing 6 and housing 4 on the hub 4, the flange 10 of the hub 4 is provided with holes 56 for receiving the studs 20 and a shallow annular relief 58 at the holes 56 (Figs. 2 and 3). The relief 58 opens away from the housing 4 and extends circumferentially along the flange 10 without interruption. The holes 56 open into the relief 58.

To machine the outboard face of the flange 10 in order to produce the machined mounting surface 22, the housing 4 is inserted into and clamped within a stationary chuck 64 so that the housing 4 remains in a fixed position (Fig. 2). Next, the hub 2 is engaged with a rotary drive 66. The engagement may occur within the bore 14 of spindle 12 and from either end of the bore 14 (access from one end shown in full lines in Fig. 2, access from the other end shown in interrupted lines). This type of engagement is particularly suitable when the bore 14 contains a spline as it will if the hub 2 is to be coupled to the drive train of the vehicle so that the road wheel W actually propels the vehicle. On the other hand, the drive 66 may include a dog 68 (shown in interrupted lines in Fig. 2) which engages the flange 10 at one of its holes 56, all without obstructing the outboard face of the flange 10. The rotary drive 66 turns the hub 4, causing it to rotate about the axis X. The axis X remains stable because the chuck 64 firmly grips the housing 4 and the bearing 6 operates in preload. With the hub 4 rotating, a cutting or facing tool 70 is advanced generally radially across the outboard face of the flange 10. The facing tool 70 removes metal from the flange 10, both radially outwardly and radially inwardly from the relief 58, and produces the machined mounting surface 22. That surface 22 is slightly conical and concave, is projecting farthest at the periphery of the flange 10. A

rotating grinding wheel may be run over the machined surface 22 to improve its finish and precision.

The mounting surface 22 on the flange 10 fixes the orientation of the brake disk B with respect to the axis X. In this regard the brake disk B contains  
5 (Fig. 1) holes 74 which are arranged in the pattern of the studs 20 and are only slightly larger than the threaded shanks of the studs 20, so that the brake disk B fits over the studs 20. Indeed, the disk B in the region of its holes 74 has a machined reference surface 76 which is planar. The machined reference surface 76 of the disk B initially abuts the machined mounting surface 22 on the flange  
10 10 of the hub 4 at the periphery of the mounting surface 22 owing to the concavity of the surface 22. But the nuts 24, when turned down, draw the reference surface 76 of the disk B against the mounting surface 22, and insure that the reference surface 76 seats firmly against the mounting surface 22 at the periphery of the latter. The disk B also has two machined friction surfaces 78  
15 that lie outwardly from the reference surface 76. The friction surfaces 78 occupy planes that are generally perpendicular to the axis X. All three surfaces 76 and 78 are machined with precision.

The brake disk B is relatively small and its reference surface 76 and friction surfaces 78 can be machined with relative ease and with considerable  
20 precision. The lug nuts 24 secure the brake disk B firmly to the hub 2 of the hub assembly A with the reference surface 76 of the brake disk B firmly abutting the mounting surface 22 on the flange 10 of the hub 4. As a consequence, the brake disk B rotates relative to the housing 4 with essentially no runout at the friction surfaces 78.

25 The outboard face of the flange 10 on the hub 2 may also be machined while the threaded studs 20 are in the flange 10 (Fig. 4). This requires two facing tools 80 and 82, the former being located radially outside of the shallow relief 58 and the latter being located within the relief 58. The tool 80 moves inwardly from the periphery of the flange 10 and produces that region of the  
30 machined mounting surface 22 that lies radially outwardly from the relief 58. The tool 82 moves inwardly from the shallow relief 58 and produces that region



of the machined mounting surface 22 that lies radially inwardly from the shallow relief 58.

This invention is intended to cover all changes and modifications of the example of the invention herein chosen for purposes of the disclosure which do  
5 not constitute departures from the spirit and scope of the invention.

Claims:

1. A process for rendering a hub assembly more suitable for accepting a brake disk having friction surfaces, the hub assembly including a hub having a spindle and a flange at one end of the spindle, a housing around the spindle of the hub and generally behind the flange, and an antifriction bearing located between the spindle and the housing and establishing an axis of rotation for the hub; said process comprising: holding the housing fast; rotating the hub on the bearing while the housing is held, with the rotation being about the axis of the bearing; and while the hub rotates, machining the face of the flange that is presented away from the housing to provide a mounting surface against which the brake disk may be installed.
2. The process according to claim 1 wherein machining includes moving a cutting tool over the face of the flange.
3. The process according to claim 1 wherein the bearing has rolling elements organized in two rows and raceways along which the rolling elements roll, with the raceways being oblique to the axis and oriented such that the bearing transfers between the housing and spindle radial loads as well as thrust loads in both axial directions.
4. The process according to claim 3 wherein the bearing is in preload, whereby no radial or axial play exists within it.
5. The process according to claim 1 wherein the flange has holes that extend axially through it; and wherein the process further comprises installing threaded studs in the holes after the mounting surface is provided.
6. The process according to claim 1 wherein the flange has an annular relief that opens out of the face of the flange that is presented away from the housing; wherein the flange further has holes which extend axially through it and open out of the annular relief; and wherein the machining includes advancing a cutting tool over the face of the flange both inside and outside the annular relief.
7. The process according to claim 6 and further comprising installing threaded studs in the holes in the flange.

-10-

8. The process according to claim 7 wherein the cutting tool is advanced across the flange after the threaded studs are installed in the holes.

9. The process according to claim 8 wherein the step of machining the face of the flange comprises advancing a first cutting tool across the flange  
5 between the periphery of the flange and the annular relief and advancing a second cutting tool across the flange between the annular relief and the axis.

10. A process for manufacturing an automotive hub assembly, said process comprising: installing a housing and an antifriction bearing over a spindle on a hub that also includes a flange which is attached to one end of the  
10 spindle, all such that the flange is located in front of the housing; capturing the bearing on the spindle; holding the housing in a fixed position; rotating the hub about the axis of the bearing; and while the hub is rotating, machining a face of its flange.

11. The process according to claim 10 wherein the bearing has  
15 rolling elements organized in two rows and raceways along which the rolling elements roll, with the raceways being oblique to the axis and oriented such that the bearing transfers between the housing and the spindle radial loads as well as thrust loads in both axial directions.

12. The process according to claim 11 wherein the bearing is in  
20 preload, whereby no axial or radial free motion exists between the housing and the hub.

13. The process according to claim 12 wherein the flange has holes which extend axially through it; and further comprising installing threaded studs in the holes such that they project beyond the face of the flange that is presented  
25 away from the housing.

14. The process according to claim 13 wherein the flange of the hub also has an annular relief which opens out of the face of the flange that is presented away from the housing, and the holes in the flange open into the relief.

30 15. The process according to claim 14 wherein the step of machining the face of the flange occurs before the threaded studs are installed in the flange

and comprises advancing a cutting tool across the face of the flange that is presented away from the housing.

16. The process according to claim 14 wherein the step of machining the face of the flange occurs after the threaded studs are installed in the flange and comprises advancing a first cutting tool over the face of the flange that is located radially outwardly from the annular relief and advancing a second cutting tool over the face of the flange that is located radially inwardly from the relief.

17. The process according to claim 13 and further comprising installing a brake disk over the thread studs and against the machined mounting surface of the flange of the hub, the brake disk having a machined reference surface that is against the machined mounting surface of the flange and machined friction surfaces that are located radially outwardly from the reference surface

18. A hub assembly for facilitating rotation about an axis, said hub assembly comprising: a hub having a flange and a spindle projecting from the flange, the flange having a generally radially directed mounting surface that is presented away from the spindle; a housing surrounding the spindle of the hub and located behind the flange; an antifriction bearing located between the spindle of the hub and the housing and being configured to transfer radial loads between the hub and housing and also thrust loads in both axial directions; and wherein the mounting surface of the flange or the hub is machined and the machining occurred on the assembled hub assembly, with the hub rotating on the bearings.

19. A hub assembly according to claim 18 wherein the spindle has shoulders at its ends; wherein the bearing includes first and second inner races located around the spindle between the shoulders and having first and second inner raceways, respectively, which are presented outwardly away from the axis and oriented obliquely to the axis, first and second outer raceways located in the housing around and presented toward the first and second inner raceways, respectively, and also oriented obliquely to the axis, and rolling elements

-12-

arranged in first and second rows between the first raceway and the second raceways, respectively; and wherein the bearing is in a condition of preload.

20. A hub assembly according to claim 19 wherein one of the shoulders is on the flange and the other is on a spindle end that is formed  
5 integral with the spindle after the inner races are installed on the spindle.

1/3




FIG. 1



3/3




FIG. 4



## INTERNATIONAL SEARCH REPORT

International Application No:  
PC US 00/14187A. CLASSIFICATION OF SUBJECT MATTER  
B23B5/02,B60B27/00According to International Patent Classification (IPC) or to both national classification and IPC<sup>7</sup>

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 98/38436 A1 (VARGA BRAKES, INC.) 03 September 1998, fig. 5.	1-5, 7, 10-13, 17, 18
A	US 5842388 A (VISSER et al.) 01 December 1998, abstract.	1-5, 7, 10-13, 17, 18

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "Z" document member of the same patent family

Date of the actual completion of the international search

10 August 2000

Date of mailing of the international search report

04.10.2000

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

LEBZELTERN

**ANHANG**

Zum internationalen Recherchenbericht über die internationale Patentanmeldung Nr.

In diesem Anhang sind die Mitglieder der Patentfamilien der im obengenannten internationalen Recherchenbericht angeführten Patentdokumente angegeben. Diese Angaben dienen nur zur Unterrichtung und erfolgen ohne Gewähr.

**ANNEX**

To the International Search Report to the International Patent Application No.

PCT/US 00/14187 SAE 286699

This annex lists the patent family members relating to the patent documents cited in the above-mentioned search report. The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

**ANNEXE**

Au rapport de recherche international relatif à la demande de brevet international n°

La présente annexe indique les membres de la famille de brevets relatifs aux documents de brevets cités dans le rapport de recherche international visée ci-dessus. Les renseignements fournis sont donnés à titre indicatif et n'engagent pas la responsabilité de l'Office.

Im Recherchenbericht angeführte Patentdokumente Patent document cited in search report Document de brevet cité dans le rapport de recherche		Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets		Datum der Veröffentlichung Publication date Date de publication
WO A1	9838436	03-09-1998	AU A1	66706/98	18-09-1998
			US A	5937499	17-08-1999
			US A	5899305	04-05-1999
			US A	5915502	29-06-1999
US A	5842388	01-12-1998	none		

For more details about this annex see Official Journal of the European Patent Office, No. 12/82.

- 1 -